
Product Family of Cold Rolling Process

Gauge Head
Display
Power
Protection
Cooling
Alarm & Report




cable upon customer requirement

	LENGTH	PART NUMBER	DESCRIPTION
CABLE	10m	00053CF001	BT42HD_010m Cable
	20m	00053CF002	BT42HD_020m Cable
	40m	00053CF003	BT42HD_040m Cable
	60m	00053CF004	BT42HD_060m Cable

UNCURBED TOLERANCES ANGULAR X. ±0.20mm ±15' .0 ±0.10mm .00 ±0.05mm .000 ±0.02mm	UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE IN MM	TITLE: CRP i4 Product Family	DRAWING No.: 00059SD004
UNCURBED SURFACE ROUGHNESS 32	BREAK ALL BURRS AND SHARP EDGES		MATERIAL: -
	FIRST ANGLE PROJECTION	QUANTITY: – / WEIGHT: – / SCALE: 1:1	ASSEMBLY No.: –
DRAWN / PROGRAM			
CHECKN / STANDARD		Proton Products International	ISSUE 1.5 / REC.DOC
AUDIT / APPROVED			SHEET 1 OF 1 / A2

Product Family of Continuous Casting Process



cable upon customer requirement

	LENGTH	PART NUMBER	DESCRIPTION
CABLE	10m	00053CF001	BT42HD_010m Cable
	20m	00053CF002	BT42HD_020m Cable
	40m	00053CF003	BT42HD_040m Cable
	60m	00053CF004	BT42HD_060m Cable

UNCURBED TOLERANCES ANGULAR X. ±0.20mm ±15' .0 ±0.10mm .00 ±0.05mm .000 ±0.02mm UNCURBED SURFACE ROUGHNESS 32	UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE IN MM BREAK ALL BURRS AND SHARP EDGES FIRST ANGLE PROJECTION	TITLE CCP i4 Product Family	DRAWING No. 00059SD003 MATERIAL -
DRAWN	PROGRAM	QUANTITY: –	WEIGHT: –	SCALE: 1:1	ASSEMBLY No.: –
CHECKN	STANDARD	Proton Products International	ISSUE: 1.8	REC.DOC
AUDIT	APPROVED		SHEET: 1 OF 1	A2

Product Family of Harsh Industrial Process

Gauge Head
Display
Power
Protection
Cooling
Alarm & Report

SLM6060 i4 00059MC004
SLM120120 i4 00059MC006

Push-In Fitting (SL/SLR)
00041MC226

SLRM6060 i4 00059MC014
SLRM120120 i4 00059MC016

AirWipe (SLM/SLRM i4)
00041MC238

A1 Alarm Unit
00025MC001

M16AP_003m(9.8ft) Cable 00025CB003
M16AP_005m(16ft) Cable 00025CB005
M16AP_010m(32ft) Cable 00025CB010
M16AP_020m(65ft) Cable 00025CB020
M16AP_030m(98ft) Cable 00025CB030

Panel Mounting Kit (CDI4)
00049MC043

CDI4
00049MC021

DB44_003m(9.8ft) Cable 00053CE001
DB44_005m(16ft) Cable 00053CE002
DB44_010m(32ft) Cable 00053CE003
DB44_020m(64ft) Cable 00053CE004
DB44_030m(98ft) Cable 00053CE005

BT42HD_010m Cable
00053CF001

Connector Box
(SL/SLRM-BT100 i4)
00059MC046

CAN 9DD_003m(9.8ft) Cable 00041CB003
CAN 9DD_005m(16ft) Cable 00041CB005
CAN 9DD_010m(32ft) Cable 00041CB010
CAN 9DD_020m(65ft) Cable 00041CB020
CAN 9DD_030m(98ft) Cable 00041CB030

PSU BOB SL i4
00060MC050

BT100 SL i4
00059MC048

USB-RS232 (1.8m) Cable
GP00000624

PC

PCIS-SL/SLR I4
00060SW001

S-BOX Connecting Panel
(With HD Connector)
00046MC266

S-BOX Connecting Panel
(With Phoenix Gland)
00046MC265

S-BOX Connecting Panel
(With VORTEX Cooler and HD Connector)
00046MC264

S-BOX Connecting Panel
(With VORTEX Cooler and Phoenix Gland)
00046MC263

S-BOX-C
00046MC324

S-BOX
00046MC230

3D Adapter (S-BOX-C)
00046MC330

3D Adapter (S-BOX)
00046MC255

Air Filter
00043MC048

Air Service Uint
00041MC370

Mains Cable
(Chinese Standard)
00001CM615

Mains Cable
(European Standard)
00003CM506

Mains Cable
(American Standard)
00002CM502

cable upon customer requirement

	LENGTH	PART NUMBER	DESCRIPTION
CABLE	10m	00053CF001	BT42HD_010m Cable
	20m	00053CF002	BT42HD_020m Cable
	40m	00053CF003	BT42HD_040m Cable
	60m	00053CF004	BT42HD_060m Cable

UNCURBED TOLERANCES ANGULAR
X. ±0.20mm ±15'
.0 ±0.10mm
.00 ±0.05mm
.000 ±0.02mm
UNCURBED SURFACE ROUGHNESS

UNLESS OTHERWISE SPECIFIED
ALL DIMENSIONS ARE IN MM
BREAK ALL BURRS AND SHARP EDGES
FIRST ANGLE PROJECTION

DRAWN
CHECKN
AUDIT
PROGRAM
STANDARD
APPROVED

TITLE
HIP i4 Product Family

DRAWING No.
00059SD002
MATERIAL
-
QUANTITY | WEIGHT | SCALE
– | – | 1:1
ASSEMBLY No.
–

Proton Products International

ISSUE 1.9 | REC.DOC
SHEET 1 OF 1 | A2